

Rev 1.1 - 1 August 2009

DATA SHEET

Newton MultiPlug

Newton MultiPlug has been engineered to give a better fix in questionable substrate. It has the added benefit of having a rubber sealing grommet supplied with the plug. In very poor substrate, a pin (supplied in bags of 100 at extra cost) is inserted into the plug that expands its outer circumference by nearly 2mm to tighten the plug into the substrate. The MultiPlug is pre-drilled to accept a size 10 (5mm) self-tapping screw for the fixing of battens or other dry-lining systems.

Size (Width x Length) **10mm x 60mm**

Quantity Per Bag **100**

Order Code **A1**



Pins for MultiPlug (Expands Plug in Poor Substrate)

Quantity Per Bag **100**

Order Code **A4**

Newton Nuseal Plug

Newton Nuseal Plugs are used to secure Newton System 500 membranes to building substrate and to fix battens or tracking systems. Prior to using Nuseal plugs, wrap a bead of Newton Waterseal Rope around the head of the plug to form a compression seal. Nuseal Plugs are recommended when applying Newton 508 or 508 Mesh to vaulted arches.

Size (Width x Length) **30mm x 70mm (11mm drill bit)**

Quantity Per Bag **100**

Order Code **A2 (Red), A3 (White)**

